


UBS

Universal Command System
for the GfA door controls TS 970, TS 971 and TS 981

- Non-interchangeable plug-in connections for accessories, such as push button, photo cell, pull-switches, etc.
- Easy, fast, fail-safe connection
- Flexible installation by several cable lengths of 3 to 20 metres
- Freely-selectable ports
- Connection can also be carried out by non-professionals



Designation	Description	Part no.
UBS junction module	1 5 ports for fitting UBS accessories	30004648
Receiver with UBS plug-in connection	2 434 MHz, dip-switch coding Supply voltage 24 V DC 1-channel EKX 1M (for TS 970) 2-channel EKX 2M ¹⁾ (for TS 981)	40014953 40014856
Three push button with UBS plug-in connection No. 31 UBS aP (wall-mounting)	3 Plastic housing, protection class IP65 Dimensions W x H x D [mm]: 72 x 138 x 48 To be used with TS 981 Selectable OPEN command for inside / outside	40014992
Key switch with UBS plug-in connection No. 420 UBS aP (wall-mounting)	4 Metal housing, protection class IP54 Dimensions W x H x D [mm]: 70 x 130 x 65 To be used with TS 981 selectable OPEN commands for inside / outside	40014994
Polarised reflex photo cell with UBS plug-in connection	5 With reflector and mounting bracket; Range 7,5 m; Protection class IP65; Voltage 24 V DC; with UBS cable: 1,5 m	30004653
UBS system cable with fitted plug on either side, and 2 cable glands	6 Length 3 m 5 m 7 m 10 m 15 m 20 m Cable glands for UBS, 10 pc	20003031.00300 20003031.00500 20003031.00700 20003031.01000 20003031.01500 20003031.02000 30004652

■ 1) The two channels can only be used for OPEN commands (TS 981 with two-way traffic control)