


Electrical accessories

Loop detectors (loop laying carried out by customer onsite)



Designation	Description	W x H x D [mm]	Part no.
Loop detector	1 1-channel to be fitted into a housing; Supply voltage 100 V - 240 V; IP20	38 x 75 x 71	40015427
Loop detector	2 2-channel to be fitted into a housing; Supply voltage 100 V - 240 V; IP20	38 x 75 x 71	40015882
Loop detector	3 1-channel in housing; Supply voltage 100 V - 240 V; IP66	75 x 125 x 125	30001266
Loop detector	4 2-channel in housing; Supply voltage 100 V - 240 V; IP66	75 x 125 x 125	30002517

Timer



Designation	Description	W x H x D [mm]	Part no.
Weekly timer "AlphaRex"	5 1-channel to be fitted into a housing; for door controls TS 970/TS 971/TS 981; Supply voltage 230 V, IP66	75 x 125 x 125	30002255
Yearly timer	6 1-channel to be fitted into a housing; for door controls TS 970/TS 971/TS 981; Supply voltage 230 V, IP66; via Bluetooth programmable	125 x 175 x 150	30002464

Photo cells



Designation	Description	Part no.
Polarised reflex photo cell	7 With 5 m connecting cable; range 7.5 m, Reflector, mounting bracket; Voltage 24 V - 240 V AC/DC; IP66	40014429
Reflector as a spare part	8	40015033
Polarised reflex photo cell ATEX	9 Ex II 2G Ex ia op IIC T4 Gb Range 10 m, reflector, mounting bracket; Voltage 5 V - 15 V DC; IP66 To be used with door control TS 971-Automatic ATEX	30005772
Through photo cell	10 Range 25 m, transmitter, receiver, 2 mounting brackets; Voltage 24 V - 240 V AC/DC; IP66	40014432

■ Safety photo cell for protection against drawing-in see page 9.014

Radar detector



Designation	Description	W x H x D [mm]	Part no.
Herkules 2	11 Voltage 12 V - 28 V AC / 12 V - 36 V DC; IP65	134 x 82 x 75	40015923
Remote Control	12 IR remote control for radar detector Herkules 2		40015924

Gearbox-heating



Designation	Description	Part no.
Gearbox-heating with automatic temperature regulation	13 Max. heating capacity 50 W (0,271 A), 230 V, IP65; For later fitting to all ELEKTROMATEN from 06.2005 onwards (not suitable for SIK- / ATEX- / FS-ELEKTROMATEN), for use at temperatures below -5 °C; when used with the SG115 series, 2 heaters are recommended	20002766.00002